

# Surface Preparation



## DYNAMITE POOL PATCH

### Sets Underwater for Swimming Pool Repairs

Dynamite Pool patch is a mixture of speciality cement and proprietary additives that permits underwater patching and general concrete repair work to be done instantly. Dynamite Pool patch can be used wherever a quick setting caulking or plugging material is needed.

(When not underwater.)

#### MANUFACTURER:

SGM, Inc.  
1502 SW 2nd Place  
Pompano Beach, FL 33069-3220  
(800) 641-9247  
(954) 943-2288  
Fax: (954) 943-2402  
www.sgm.cc  
sales@sgm.cc

#### TECHNICAL DATA:

To date, no specifications have been industry approved. Our material is tested and certified by independent laboratories. All data is given in good faith, however, we reserve the right to change products and specifications without notice. SGM advises interested parties to satisfy themselves as to the accuracy of any data and seek certification if appropriate.

#### USES:

- Underwater pool repair
- Underwater concrete repair
- New construction
- Remodeling

#### PACKAGING:

3lbs.(1.36kg), 9lbs.(4.09kg),  
60lbs (27.24kg)

#### CHARACTERISTICS:

- High Strength
- Sets underwater
- Brilliant white

#### SURFACE PREPARATION:

Repair area must be clean and free of any paint, dust or grease, Chisel V-shaped channel to allow easy application wherever possible. Dampen area prior to application.

#### APPLICATIONS:

Mix approximately one (1) part water to three (3) parts Dynamite Pool Patch while stirring continuously or until material has a dough like consistency.

**Warning:** Warm water will accelerate set time of patch. Mix only as much as can be used in 3-5 minutes. Using a steel trowel or pointed tool, force material into hole or crack. To repair water leaks or for under-water use, apply pressure for a minimum of five (5) minutes or until material has firmly set. Dampen material for 15 minutes after patching to prevent cracking.

#### WARNING:

**Eye Irritant:** Contains Portland cement product is alkaline on contact with water. Use paddle for mixing to avoid splashing into eyes or contact with skin. During mixing or application, avoid contact with eyes. In case of such contact, flood eyes repeatedly with water and CALL PHYSICIAN. Wash thoroughly after handling and before smoking or eating. Do not take internally. **WARNING:** This product can expose you to chemicals including silica, which is known to the State of California to cause cancer. For more information go to [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov). Wear NIOSH approved mask for Silica dust. **KEEP OUT OF REACH OF CHILDREN.**

#### SHELF LIFE:

Up to six months from date of manufacturing in unopened container

#### WARRANTY:

SGM Inc. warrants this product will perform in accordance with its intended

use for a period of six months from the date of manufacture. Any claim for defective product must be submitted in writing to SGM Inc. and samples of defect must be provided. SGM Inc. sole obligation will be to replace any product determined to be defective by SGM Inc. **IN NO EVENT SHALL SGM INC. BE LIABLE FOR DAMAGES OF ANY KIND OR NATURE, WHETHER ARISING BY CONTRACT, TORT OR OTHERWISE.** SGM INC.'S SOLE OBLIGATION WILL BE TO REPLACE ANY PRODUCT DETERMINED BY SGM INC. TO BE DEFECTIVE. Your acceptance or use of this product is your agreement Broward County, Florida, and Florida law is the exclusive jurisdiction and venue for all purposes.

#### TECHNICAL SERVICES:

Technical assistance, including more detailed information, product literature, test results, project list, samples, assistance in preparing project specifications and arrangements for job site inspection and supervision, is available by contacting Technical Services Department.

(800) 641-9247  
(954) 943-2288  
Fax: (954) 943-2402  
www.sgm.cc  
ts@sgm.cc



**WARNING:** This product can expose you to chemicals including silica, which is known to the State of California to cause cancer. For more information go to [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov).

[www.sgm.cc](http://www.sgm.cc)

800.641.9247

