



101 WHITE
● ■ + ▲



126 CRÈME
● ■ +



119 OYSTER
● ■ +



102 ANTIQUE
● ■ + ▲



127 BEACH
● ■ +



129 SUNGLOW
● ■ +



103 LIGHT SAND
● ■ +



337 CANVAS
● ■ + ♣



200 BUFF
● ■ +



124 SEA SHELL
● ■ +



400 HONEY
● ■ +



125 CHAMPAGNE
● ■ +



338 KHAKI
● ■ + ♣



106 SADDLE
● ■ +



105 AZTEC GOLD
● ■ +



420 MOCHA
● ■ +



430 CHOCOLATE
● ■ +



109 ALMOND
● ■ +



204 TAWNY
● ■ +



325 KOALA
● ■ +



153 LIGHT BUCKSKIN
● ■ +



300 SAND DUNE BEIGE
● ■ + ♣



205 BURLAP
● ■ + ▲



206 ASH
● ■ +



207 DELOREAN GRAY
● ■ +



315 DOVE GRAY
● ■ + ▲



114 CHARCOAL BLACK
● ■ + ▲



108 NATURAL GRAY
● ■ + ▲



121 SILVER
● ■ + ▲



208 PALE LINEN
● ■ +



209 GLACIER BLUE
● ■ + ♣



210 EMERALD ICE
● ■ + ♣



SECURITY (SANDED) POLYMER MODIFIED GROUT

Polymer modified Portland cement based grout is designed to be used with all tile types in joint widths from 1/8" to 5/8". Eliminates the need for liquid additives with its advanced polymer technology, easy clean-up and eliminates shading. Meets ANSI A118.7 standards.

DRY SET (UNSANDED) POLYMER MODIFIED GROUT

To be used when grout joints are 1/8" or less when installing glazed bodied tiles, marble or granite. Note: Shade variations may occur due to absorbency of the tile. When grout is wet, color will appear darker. Meets ANSI A118.7

COLOR GUARD GROUT STAIN

Unique concept in grout and concrete coatings. Sinks deeply into pores, coating the aggregate and leaving the color below the wearing surface. Dries to a matte finish which maintains the granular appearance of grout and provides a glare free, non-skid uniform color that is highly resistant to wear, sunlight, water and extreme temperature.

EGS MORTAR & GROUT SYSTEM

This 100% solid epoxy grout & mortar is highly chemical, stain resistant & yields exceptionally high strengths. A water cleanable, three component, mortar and grout system designed for setting and grouting ceramic tile and pavers over a wide variety of substrates. Ideal for use in food service locations, laboratories & similar environments. Meets ANSI A118.3

COLOR CAULK

A premium quality sealant that provides a long-lasting water-resistant seal. It is formulated with silicized acrylic to provide a flexible, mildew-resistant, stain-resistant, crack-resistant high adhesion product. Matches all SGM sanded and non-sanded grout colors.

SGM offers the very best installation systems available in the industry. Customer and Technical assistance is just a phone call away. You can also visit our website at www.sgm.cc to learn more about new innovations, product information and technical support.

You can rest assured that the highest quality materials have been used and are supported by the best warranty program in the industry. It's a sign of our commitment to achieve the highest quality standards in all our installation systems.



Joint Width Square Foot Coverage Per 25Lb. Bag									
Nominal Tile Size	1/16" NS	1/8" NS	1/8" S	3/16" S	1/4" S	3/8" S	1/2" S	EGS 1/8"	EGS 1/4"
1" X 1" X 1/4"	105	57	56	-	33	25	-	30	17
2" X 2" X 1/4"	202	105	103	-	57	41	-	55	30
3" X 3" X 1/4"	298	153	151	-	81	57	-	81	43
4 1/4" X 4 1/4" X 1/4"	419	214	-	-	-	-	-	113	58
4" X 8" X 3/8"	-	-	-	-	92	63	49	93	48
6" X 6" X 5/16"	470	238	-	-	-	-	-	-	-
6" X 6" X 1/2"	-	-	194	-	76	52	40	78	40
6" X 24" X 3/8"	-	-	-	213	161	110	-	-	-
6" X 36" X 3/8"	-	-	-	227	172	117	-	-	-
8" X 8" X 3/8"	-	-	263	-	134	91	70	138	71
8" X 24" X 3/8"	-	-	-	264	200	135	-	-	-
8" X 36" X 3/8"	-	-	-	288	217	147	-	-	-
10" X 10" X 3/8"	-	-	327	-	166	113	86	172	89
12" X 12" X 3/8"	-	-	392	-	199	134	102	206	105
13" X 13" X 3/8"	-	-	424	-	215	145	110	223	113
16" X 16" X 3/8"	-	-	520	349	263	177	134	274	138
18" X 18" X 3/8"	1164	585	585	392	295	199	150	308	155
20" X 20" X 3/8"	1293	649	649	435	327	220	166	342	172
24" X 24" X 3/8"	1550	778	778	520	392	263	199	410	206



Security Polymer Grout is a registered trademark of SGM, Inc. Use of this trademark without prior written consent is prohibited.



1502 SW 2nd Place
 Pompano Beach, FL 33069
 1.800.641.9247
www.sgm.cc



www.sgm.cc



Snap to use our Grout Coverage Calculator online

We exceed industry standards, to deliver the quality you come to expect, *from start to finish.*

Sample colors are as accurate as modern technology can produce. Final grout color may vary due to job site conditions, tile porosity, mixing ratio, installation methods, sample colors or individual batches. Use grouts with the same lot/batch number. Different lot/batch numbers should be dry blended to obtain color uniformity. Verify appearance with a test area before installation. Some tiles or stones might be stained by colored grouts, application of a grout release may be necessary. Since SGM has no control over the installation procedure of this product, the manufacturer disclaims any and all warranties, expressed or implied regarding color, shade and appearance of the product, at all times, and after opening the container. Manufacturer's warranty is limited to replacement of product.



POLYMER SANDED
 UNSANDED GROUTS
 EPOXY • CAULKS • STAINS

